

fiamma 

SINCE 1977



C O M P A S S
S I N G L E B O I L E R



S I N G L E B O I L E R

	COMPASS 1 SE	COMPASS 2 SE COMPACT	COMPASS 2 SE	COMPASS 3 SE
Groups Grupos	1	2	2	3
Temperature control Controlo de temperatura	PID	PID	PID	PID
Digital management Gestão digital	yes/ sim	yes/ sim	yes/ sim	yes/ sim
Shot timer	yes/ sim	yes/ sim	yes/ sim	yes/ sim
Boiler technology Tecnologia de caldeira	SINGLE BOILER HEAT EXCHANGER / CALDEIRA COM SISTEMA TERMOSSIFÓNICO			
Boiler capacity Capacidade da caldeira	5 l	6 l	11 l	18 l
Power Potência	1.95 kW	2.7 kW	3.7 kW	5.2 kW
Voltage Alimentação	~220-240 V	~220-240 V	~220-240 V	~220-240 V/ 400 V ~2 N
LED lights Iluminação LED	yes/ sim	yes/ sim	yes/ sim	yes/ sim
Steam wands Lanças de vapor	1	1	2	2
Water tap Torneira de água	1	1	1	1
Cup warmer Escalda-chávenas	-	-	yes/ sim	yes/ sim
Standard Colors Cores standard	● ○	● ○	● ○	● ○
Other colors / Customization Outras cores / Personalização	yes/ sim	yes/ sim	yes/ sim	yes/ sim
Automatic cleaning Limpeza automática	yes/ sim	yes/ sim	yes/ sim	yes/ sim
Dimensions (Tall Cups) Dimensões (Tall Cups)	560x600x590 mm	560x600x590 mm	750x600x590 mm	960x600x590 mm
Dimensions (Small Cups) Dimensões (Small Cups)	560x600x540 mm	560x600x540 mm	750x600x540 mm	960x600x540 mm
Packaging Embalagem	710x710x750 mm	710x710x750 mm	870x710x750 mm	1080x710x750 mm
Weight (Gross/net) Peso (bruto/líquido)	54 kg / 40 kg	61 / 47 kg	76 kg / 64 kg	98 kg / 80 kg